



## 2-wire programmable transmitter

### 5333A

- RTD or Ohm input
- High measurement accuracy
- 3-wire connection
- Programmable sensor error value
- For DIN form B sensor head mounting



#### Application

- Linearized temperature measurement with Pt100...Pt1000 or Ni100...Ni1000 sensor.
- Conversion of linear resistance variation to a standard analog current signal, for instance from valves or Ohmic level sensors.

#### Technical characteristics


- Within a few seconds the user can program 5333A to measure temperatures within all RTD ranges defined by the norms.
- The RTD and resistance inputs have cable compensation for 3-wire connection.

#### Mounting / installation

- For DIN form B sensor head or DIN rail mounting with the fitting type 8421.


#### Applications

RTD to 4...20 mA



2-wire installation  
in control room

Resistance to 4...20 mA



2-wire installation  
in control room

Order:

Type
5333A

## Environmental Conditions

Operating temperature.....	-40°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree (encl./terminal).....	IP68 / IP00

## Mechanical specifications

Dimensions.....	Ø 44 x 20.2 mm
Weight approx.....	50 g
Wire size.....	1 x 1.5 mm <sup>2</sup> stranded wire
Screw terminal torque.....	0.4 Nm
Vibration.....	IEC 60068-2-6
2...25 Hz.....	±1.6 mm
25...100 Hz.....	±4 g

## Common specifications

### Supply

Supply voltage.....	8.0...35 VDC
Internal power dissipation.....	25 mW...0.8 W

### Response time

Response time (programmable).....	0.33...60 s
Voltage drop.....	8.0 VDC
Warm-up time.....	5 min.
Programming.....	Loop Link
Signal / noise ratio.....	Min. 60 dB
Accuracy.....	Better than 0.1% of selected range
Signal dynamics, input.....	19 bit
Signal dynamics, output.....	16 bit
Effect of supply voltage change.....	< 0.005% of span / VDC
EMC immunity influence.....	< ±0.5% of span

## Input specifications

### Common input specifications

Max. offset.....	50% of selected max. value
------------------	----------------------------

### RTD input

RTD type.....	Pt100, Ni100, lin. R
Cable resistance per wire (max.).....	10 Ω
Sensor current.....	> 0.2 mA, < 0.4 mA
Effect of sensor cable resistance (3-wire).....	< 0.002 Ω / Ω
Sensor error detection.....	Yes

### Linear resistance input

Linear resistance min...max.....	0 Ω...10000 Ω
----------------------------------	---------------

## Output specifications

### Current output

Signal range.....	4...20 mA
Min. signal range.....	16 mA
Load (@ current output).....	≤ (Vsupply - 8) / 0.023 [Ω]
Load stability.....	≤ 0.01% of span / 100 Ω
Sensor error indication.....	Programmable 3.5...23 mA
NAMUR NE 43 Upscale/Downscale.....	23 mA / 3.5 mA

### Common output specifications

Updating time.....	135 ms
*of span.....	= of the presently selected range

## Observed authority requirements

EMC.....	2014/30/EU
----------	------------

## Approvals

ATEX 2014/34/EU.....	KEMA 10ATEX0003 X
IECEx.....	DEK 13.0036X
INMETRO.....	DEKRA 13.0002 X
CCOE.....	P337392/3
EAC.....	TR-CU 020/2011
DNV-GL Marine.....	Stand. f. Certific. No. 2.4

## Additional Documents Link

User Manual: <http://www.itsirl.com/datasheets/5333A MANUAL.pdf>

ATEX Cert: <http://www.itsirl.com/datasheets/5333A ATEX CERT.pdf>

IEC Cert: <http://www.itsirl.com/datasheets/5333A IEC.pdf>

Conformity: <http://www.itsirl.com/datasheets/5333ACONF.pdf>